Vendor: Dell-EMC

Exam Code: D-PDD-DY-01

Exam Name: Dell PowerProtect Data Domain Deploy v2

Version: DEMO

QUESTION 1
What is the default password for iDRAC root user on a Dell PowerProtect Data Domain appliance?

A. System Serial Number
B. Express Service Code
C. Service Tag
D. QR code

Answer: A
Explanation:
The default password for the iDRAC root account on a PowerProtect Data Domain appliance is the system serial number, found on the Product Serial Number Tag (PSNT).

QUESTION 2
Your customer requires that no Dell PowerProtect Data Manager backups are deleted, but they also want the flexibility to modify the expiration period once a legal hold is lifted. Which Dell PowerProtect Data Domain feature would meet the customer's needs?

A. Retention Lock Governance
B. Locking the File System
C. Cloud Tier
D. Retention Lock Compliance

Answer: A
Explanation:
Governance mode prevents backups from being deleted during the retention period while allowing an authorized administrator to reduce or override retention after the legal hold is lifted. Compliance mode does not permit early reversal.

QUESTION 3
Which Dell PowerProtect Data Domain appliance requires a deep rack?

A. DD9410
B. DD9910F
C. DD6410
D. DD9910

Answer: C
Explanation:
The DD6410 is 83.6 cm (32.9 in) deep, so it requires a deep rack. The DD9410, DD9910, and DD9910F controllers are approximately 72.4 cm (28.5 in) deep.

QUESTION 4
A technician is installing a PowerProtect DD6410 system with two ES120 expansion shelves. Which two installation guidelines must be followed to ensure proper setup? (Choose two.)

A. Install all shelves from top to bottom
B. Use 1-2 meter cables for head-to-shelf connections
C. Use 0.5 meter cables for shelf-to-shelf connections

D. Fill the rack completely with no remaining space

Answer: AB
Explanation:
The intended guidance is to maintain a consistent shelf order and use appropriately sized controller-to-shelf SAS cables. However, Dell's current two-ES120 cabling table specifies 2 m and 3 m cables.

QUESTION 5
An implementation engineer must enable immutable backup protection on a Dell PowerProtected Data Domain MTree. What is the first step in performing this task?

A. Verify DD Retention Lock Compliance is licensed
B. Create a Secure iDRAC User with Security Officer Role
C. Set up administrator and a security officer accounts
D. Enable Retention Lock Governance mode on the MTree

Answer: A
Explanation:
Retention Lock is a licensed feature. Before configuring security-officer authorization and enabling Compliance mode on the system and MTree, the engineer must confirm that the Retention Lock Compliance license is installed.

QUESTION 6
Before enabling Cloud Tier on a Dell PowerProtect Data Domain appliance, which two preparation steps must be completed? (Choose two.)

A. Add and configure required enclosures
B. Enable file system encryption
C. Create all cloud units
D. Add Dell Cloud Tier license

Answer: AD
Explanation:
Cloud Tier requires licensed capacity and properly configured local storage for cloud metadata before the feature is enabled. Cloud units are created afterward, and file-system encryption is not a prerequisite.

QUESTION 7
An implementation engineer added a DS600 expansion shelf with 60 drives to a Dell PowerProtect DD9410 appliance. When the enclosure show topology command is run, a redundant path is not seen. What is the reason for this discrepancy?

A. The DD9410 does not support DS600 expansion shelf
B. An unsupported SAS cable was used for the second path
C. The DS600 expansion shelf only has one SAS connection
D. Only one SAS path is connected to the controller

Answer: D
Explanation:
The DS600 requires dual SAS paths for redundancy. If enclosure show topology does not display

a redundant path, the second SAS connection to the controller is missing or not connected correctly.

QUESTION 8
Which Multi-Factor Authentication does a PowerProtect Data Domain appliance support for logging into the Dell PowerProtect Data Domain System Manager?

A. Duo Security
B. TOTP
C. RADIUS
D. RSA SecurID

Answer: D
Explanation:
PowerProtect Data Domain supports RSA SecurID as the MFA server for username-and-password logins through DD System Manager or SSH.

QUESTION 9
A customer requires strict access separation for backup administrators, users, and security teams. Which two Dell PowerProtect Data Domain features best align with this requirement? (Choose two.)

A. DD Retention Lock
B. DD Secure Multitenancy
C. Role-Based Access Control
D. DD Encryption keys

Answer: BC
Explanation:
Secure Multitenancy isolates administrative domains and backup resources, while RBAC assigns permissions according to job responsibilities such as administrator, user, and security officer.

QUESTION 10
An implementation engineer is racking a Dell PowerProtec DD9410 appliance. Which expansion shelf option is supported?

A. Two DS600 shelves
B. Five DS600 shelves
C. Four ES40 shelves
D. Eight ES40 shelves

Answer: A
Explanation:
The DD9410 supports DS600 expansion shelves, with the supported cabling design using two chains of up to two DS600 shelves. ES40 shelves are not supported for this model, and five DS600 shelves exceeds the supported configuration.

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

★ More than **99,900** Satisfied Customers Worldwide.

★ Average **99.9%** Success Rate.

★ **Free Update** to match latest and real exam scenarios.

★ **Instant Download** Access! No Setup required.

★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.

★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.

★ **100%** Guaranteed Success or **100%** Money Back Guarantee.

★ **Fast**, helpful support **24x7**.

View list of all certification exams: http://www.lead2pass.com/all-products.html

10% Discount Coupon Code: **ASTR14**