



Vendor: HP

Exam Code: HP2-Z19

Exam Name: Implementing HP Network Security Solutions

Version: DEMO

QUESTION 1

Which E-Series CLI commands enable you to view all show commands available in the current context? (Select two.)

- A. Switch# show /?
- B. Switch# show all
- C. Switch# show help
- D. Switch# show ?
- E. Switch# show <tab>
- F. Switch# help show

Answer: DE

QUESTION 2

You are at the manager level prompt in the CLI of an HP E3500 yl switch. Which options are available at this prompt? (Select two.)

- A. assign IP address to VLAN interface
- B. enable IP routing
- C. restart the switch
- D. disable ports
- E. update software

Answer: CE

QUESTION 3

Which HP E-Series switch models display the following prompt in the interface configuration context? (Select two.) HP Switch(eth-A24)#

- A. E8212 zl
- B. E6600-24G
- C. E5412-96G zl
- D. E2910-24G al
- E. E3500-48G-POE yl

Answer: ABE

QUESTION 4

You make configuration changes to the running configuration of your HP E3500 yl switch. Which command saves these changes to your startup configuration?

- A. save running-config
- B. copy running-config startup-config
- C. write memory
- D. write config

Answer: C

QUESTION 5

You must update the software on an HP E3500 zl switch. Which devices can be sources for the copy command? (Select two.)

- A. USB flash drive
- B. management workstation hard drive
- C. TFTP server
- D. FTP server
- E. Compact Flash card

Answer: AC

QUESTION 6

Refer to the exhibit below.

```
hostname "E5406"
module 1 type J8702A
vlan 1
  name "DEFAULT_VLAN"
  untagged A9-A24
  ip address 192.168.1.1 255.255.255.0
  no untagged A1-A8
  exit
vlan 5
  name "VLAN5"
  untagged A1-A4
  ip helper-address 192.168.1.2
  ip address 192.168.5.1 255.255.255.0
  exit
vlan 6
  name "VLAN6"
  untagged A5-A8
  ip helper-address 192.168.1.2
  ip address 192.168.6.1 255.255.255.0
  exit
vlan 2
  name "VLAN2"
  ip address 192.168.2.1 255.255.255.0
  exit
snmp-server community "public" unrestricted
spanning-tree
spanning-tree priority 0
```

You have configured IP helper addresses for VLAN 5 and VLAN 6 on this HP E5406 zl switch. However, users in these VLANs report that their computers are not receiving DHCP addresses. Which feature must be enabled to address this problem?

- A. DNS
- B. DHCP relay
- C. IP routing
- D. DHCP snooping

Answer: B

QUESTION 7

Refer to the exhibit below.

```
E5406# show vlan 100
```

```
Status and Counters - VLAN Information - VLAN 100
```

```
VLAN ID : 100
Name : VLAN100
Status : Port-based
Voice : No
Jumbo : No
```

Port Information	Mode	Unknown VLAN	Status
A24	Untagged	Learn	Up

```
E5406# show vlans port a24
```

```
Status and Counters - VLAN Information - for ports A24
```

VLAN ID	Name	Status	Voice	Jumbo
100	VLAN100	Port-based	No	No

You enter the following command at the switch's CLI: E5406(vl a-100)# no untag a24 Why does this command fail?

- A. Port A24 is not a member of VLAN 100.
- B. Port A24 must be a member of at least one VLAN.
- C. VLAN 100 must have at least one port member.
- D. no untag a24 is an invalid CLI command.

Answer: B

QUESTION 8

Which security technology requires that you set read/write community names?

- A. SFTP
- B. SSH
- C. SNMP
- D. HTTPS
- E. SMTP

Answer: C

QUESTION 9

What are benefits of implementing Secure Socket Shell (SSH) for remote management of HP switches? (Select two.)

- A. user accounting
- B. encryption of management traffic
- C. stronger passwords
- D. enforcement of management VLAN
- E. secure authentication
- F. encryption of all traffic

Answer: BE

QUESTION 10

Which remote management interface on an E-Series switch can be secured by enabling Secure Sockets Layer (SSL)?

- A. console
- B. menu
- C. web management
- D. Telnet

Answer: C

QUESTION 11

What is the effect of the following commands entered at the CLI of an HP E8212 zl switch with routing and RIP enabled? E8212(rip)# redistribute ospf

- A. The switch will filter OSPF routes from RIP updates received from peers.
- B. The switch will include routes learned through OSPF in all RIP updates.
- C. The switch will include routes learned through RIP in all OSPF link-state messages.
- D. The switch will give preference to OSPF routes over RIP routes in its route table.

Answer: B

QUESTION 12

Refer to the exhibit below.

IP Route Entries						
Destination	Gateway	ULAN	Type	Sub-Type	Metric	Dist.
127.0.0.0/8	reject		static		0	0

What is indicated by this entry in the IP route table of an HP E8212 zl switch?

- A. The switch has been configured with an ACL that blocks communications with the loopback interfaces.
- B. The switch does not permit communications with any loopback interface.
- C. Traffic to this interface is rejected with the single exception of traffic to the host address of the switch's loopback interface (127.0.0.1/ 32).
- D. A loopback interface is configured with 127.0.0.0.

Answer: C

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives®

10% Discount Coupon Code: ASTR14