



**Vendor:** Aruba

**Exam Code:** AWMP

**Exam Name:** Aruba Wireless Mesh Professional 4.2

**Version:** DEMO

#### QUESTION 1

What limit does receiver sensitivity describe?

- A. the maximum RSSI to decode a packet at a specific data rate
- B. the minimum RSSI to decode a packet at a specific data rate
- C. the receive signal level strength, which is always the same for each rate
- D. the maximum output transmit power for receivers that are in range
- E. the maximum RSSI to decode a packet at a specific data rate (5 - 45.45%)

**Answer: B**

#### QUESTION 2

What is the maximum percentage obstruction of the first Fresnel zone in a point to point link?

- A. 35%
- B. 40%
- C. 50%
- D. 60%

**Answer: B**

#### QUESTION 3

Which technical specifications of the antenna should be considered during selection of an antenna?

- A. Frequency range
- B. Supported data rates and modulation technologies
- C. Polarization
- D. Gain
- E. Encryption modes

**Answer: ACD**

#### QUESTION 4

Which of these statements is correct in regards to Fresnel zone and mesh network design? Choose all that apply.

- A. Mesh network design does not need to account for Fresnel zone.
- B. Fresnel zone clearance of at least 60% is required for mesh radio links.
- C. Fresnel zone only comes into play when designing Wi-Fi client coverage.
- D. Fresnel zone, Free Space Path Loss, EIRP and receive sensitivity are all factors that should be considered.

**Answer: BD**

#### QUESTION 5

Which statement is most correct and should be considered in a typical handheld client Wi-Fi access mesh design?

- A. The upstream and downstream link budgets between clients and mesh routers are symmetrical.
- B. Client devices typically broadcast at higher EIRP than mesh routers.
- C. Client EIRP and receive sensitivity is generally the limiting factor for range.
- D. Mesh backhaul links and client access should all be on the same channel to maximize connectivity.

**Answer: C**

#### **QUESTION 6**

What is the typical use for computing link budgets? Choose the most correct.

- A. Determining attainable coverage.
- B. Determining attainable range.
- C. Determining the height to mount antennas.
- D. Determining the proper aim of antennas.

**Answer: B**

#### **QUESTION 7**

Which is the least important factor to consider when designing a mesh network?

- A. which frequency of backhaul and access can be used
- B. number of 3G towers in the area
- C. power sources and grounding sources
- D. usability of the site
- E. available antenna

**Answer: B**

#### **QUESTION 8**

Which of these following is recommended to assist in creating preliminary mesh designs and is used by the Aruba Outdoor Planner?

- A. Google maps
- B. Google Earth
- C. MeshConfig
- D. Network Stumbler

**Answer: B**

#### **QUESTION 9**

Which of these identifies the folder(s) used to identify and process radio locations in the Aruba Outdoor Planner?

- A. Nodes
- B. Portals
- C. Locations

D. Routers

**Answer: C**

**QUESTION 10**

When designing mesh links what SNR value should normally be considered the minimum for a robust link?

- A. -20dBm
- B. 20 dBm
- C. 100 dBm
- D. 10 dBm

**Answer: B**

## Thank You for Trying Our Product

### Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER  
NETWORKS



EMC²  
where information lives®

**10% Discount Coupon Code: ASTR14**