



Vendor: Juniper

Exam Code: JN0-691

Exam Name: Junos Troubleshooting

Version: DEMO

QUESTION 1

You must view the /var/log/messages file from the operational mode and filter only information related to the ae0 interface. The ge-0/0/0 and ge-0/0/1 interfaces are member links of the ae0 interface.

Which command would you use to view this information?

- A. show log messages | match ae0
- B. show log messages | match "ge-0/0/0 | ge-0/0/1"
- C. show log | match ae0
- D. show log message

Answer: A

QUESTION 2

When using change-control processes, which three actions must be considered? (Choose three.)

- A. Coordinate scheduling that will be least impactful to production.
- B. Coordinate scheduling that works best with the individuals involved.
- C. Perform testing in a production environment prior to change-control.
- D. Formalize the request based on company policies.
- E. Balance troubleshooting needs with productions risks.

Answer: ADE

QUESTION 3

Referring to the exhibit, what happens to traffic sent to unknown destinations?

```
user@host> show route forwarding-table
Routing table: default.inet
Internet:
Destination      Type RtRef Next hop      Type Index NhRef Netif
default          user  0 0:24:dc:a:ac:15 ucst  567  3 ge-0/0/3.0
default          perm  0                rjct   36  1
0.0.0.0/32       perm  0                dscd   34  1
1.1.1.0/24       intf  0                rslv  558  1 ge-0/0/3.0
1.1.1.0/32       dest  0 1.1.1.0         recv  556  1 ge-0/0/3.0
1.1.1.1/32       dest  0 0:24:dc:a:ac:15 ucst  567  3 ge-0/0/3.0
1.1.1.2/32       intf  0 1.1.1.2         locl  557  2
1.1.1.2/32       dest  0 1.1.1.2         locl  557  2
1.1.1.255/32     dest  0 1.1.1.255       bcst  555  1 ge-0/0/3.0
2.2.2.0/32       dest  0 2.2.2.0         recv  586  1 ge-5/0/3.0
2.2.2.1/32       dest  0 0:24:dc:a:ac:16 ucst  574  1 ge-5/0/3.0
2.2.2.2/32       intf  0 2.2.2.2         locl  587  2
2.2.2.2/32       dest  0 2.2.2.2         locl  587  2
2.2.2.255/32     dest  0 2.2.2.255       bcst  585  1 ge-5/0/3.0
```

- A. Traffic to unknown destinations will be silently discarded.
- B. Traffic to unknown destinations uses the ge-0/0/3 interface.
- C. Traffic to unknown destinations uses the ge-5/0/3 interface.
- D. Traffic to unknown destinations will be rejected.

Answer: B

QUESTION 4

An engineer upgraded a router to an incorrect version of the Junos OS and performed the system snapshot function.

Which two actions would return the system to the original version? (Choose two.)

- A. Downgrade to the correct Junos OS version and perform a system snapshot.
- B. Rollback the Junos OS version and perform a system snapshot.
- C. Reboot the router using the secondary media and perform a system snapshot.
- D. Reboot the router using the primary media and perform a system snapshot.

Answer: AC

QUESTION 5

To protect the Routing Engine of your Junos device from denial-of-service attacks, you created a firewall filter. Where do you apply the firewall filter?

- A. input on the fxp0 interface
- B. output on the fxp0 interface
- C. input on the lo0 interface
- D. output on the lo0 interface

Answer: C

QUESTION 6

Which monitoring protocol allows you to securely monitor Junos devices?

- A. SNMPv3
- B. SNMPv1
- C. SNMPv2c
- D. SNMPv2u

Answer: A

QUESTION 7

Which statement is true about an operational interface that has been deactivated?

- A. The interface is admin down and link up.
- B. The interface is admin up and link down.
- C. The interface is admin up and link up.
- D. The interface is admin down and link down.

Answer: D

QUESTION 8

Which two statements are true about nonstop active routing? (Choose two.)

- A. Routing information is saved on the backup Routing Engine.
- B. Routing information is not saved on the backup Routing Engine.
- C. You must enable GRES for nonstop active routing to function correctly.
- D. You must enable graceful restart for nonstop active routing to function correctly.

Answer: AC

QUESTION 9

Referring to the exhibit, you must clear a user session that is not responding. The user is logged in using the console.

```
user@host> show system users
6:50PM up 12 days, 16:31, 4 users, load averages: 0.24, 0.07, 0.02
USER      TTY      FROM          LOGIN@  IDLE WHAT
host       u0       -             6:45PM      -  -cli (cli)

host       p0       10.210.14.132 6:49PM      1  -cli (cli)

host       p1       10.210.14.133 6:50PM      -  -cli (cli)
host       p2       10.210.14.138 6:53PM      -  -cli (cli)
```

Which session must be cleared?

- A. TTY session p0
- B. TTY session p2
- C. TTY session p1
- D. TTY session u0

Answer: D

QUESTION 10

You are asked to configure your MX480 device to flag a remote DTE into loopback mode. In which hierarchy would this capability be configured?

- A. [edit interfaces <interface-name> otn-options]
- B. [edit protocols mpls]
- C. [edit interfaces <interface-name> ether-options]
- D. [edit protocols oam]

Answer: D

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives[®]

10% Discount Coupon Code: ASTR14