



Vendor: Juniper

Exam Code: JN0-692

Exam Name: Juniper Networks Certified Support Professional (JNCSP-SP)

Version: DEMO

QUESTION 1

Your Junos device has the following IS-IS configuration:

```
[edit protocols isis]
user@router# show
level 1 disable;
interface ge-0/0/0 {
level 2 disable;
}
```

Which statement is true?

- A. The interface can form only L1 adjacencies.
- B. The interface can form only L2 adjacencies.
- C. The interface can form both L1 and L2 adjacencies.
- D. The interface cannot form any adjacencies.

Answer: C

QUESTION 2

In your network, you have noticed route oscillation involving an OSPF route. What is the reason?

- A. There is a duplicate router ID in the network.
- B. There is a mismatching netmask.
- C. The external preference of OSPF is 201.
- D. There is an NSSA area.

Answer: A

QUESTION 3

You notice that an EBGP peering session has terminated and no NOTIFICATION message appears in the traceoptions output. What has happened?

- A. The peer router has crashed.
- B. The peer has restarted the hold timer.
- C. The peer update message was missing essential BGP attributes.
- D. The peer state was reset to Idle.

Answer: A

QUESTION 4

R2 has an IBGP peering session with R1 but is not installing the expected external BGP routes. R1 has these same routes installed and they are active in its route table. What are two reasons for this happening? (Choose two.)

- A. local preference value
- B. cannot reach next hop
- C. misconfigured policy

D. AS path loop

Answer: BC

QUESTION 5

You have enabled MPLS in your network using LDP for control plane signaling. After completing the configurations, you find that both your input and output LDP databases have labels only for loopback interfaces.

Referring to the scenario, which two statements are correct? (Choose two.)

- A. You should verify the configurations first, then enable `ldp traceoptions`.
- B. The default egress policy for LDP in the Junos OS announces only the loopback address.
- C. An LDP egress policy must be used to create and advertise new label mappings for directly connected prefixes other than the loopback.
- D. An LDP export policy must be used to create and advertise new label mappings for directly connected prefixes other than the loopback.

Answer: BC

QUESTION 6

You have configured an MPLS LSP but it will not establish because of a failed CSPF computation. What are two reasons for this happening? (Choose two.)

- A. An indirect loose hop is specified in the ERO.
- B. BFD has been enabled for the IGP on the LSRs.
- C. Ingress and egress routers are in different OSPF areas.
- D. The path for the LSP does not have enough bandwidth available.

Answer: CD

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives®

10% Discount Coupon Code: ASTR14