

Exam Code: HP0-Y22

Exam Name: Implementing HP ProCurve MultiService

Vendor: HP

Version: DEMO

Part: A

1: You have been asked by your customer to create a wireless network in a public area with centralized user authentication. Given the following choices, which authentication method would you choose to implement?

- A.802.1X authentication
- B.MAC authentication
- C.Web authentication
- D.WEP authentication

Correct Answers: C

2: What are the key features of ProCurve Guest Management Software (formerly VMT)? (Select two.)

- A.the ability to create user logo designs
- B.the ability to perform batch creation of user accounts
- C.the ability to print X.509 certificates
- D.the ability to manage a visitor's account on MSM controllers
- E.the ability to import special programs for customer use

Correct Answers: B D

3: The MSM730 has 4 Ethernet ports; one for the LAN and another for the Internet. What is the function of the other two Ethernet ports?

- A.CLI access
- B.client connectivity
- C.reserved for future expansion
- D.uplinks

Correct Answers: C

4: ProCurve's RF Planner is made specifically for which operating system?

- A.Linux
- B.MAC OS
- C.Microsoft Windows
- D.Sun Microsystems Solaris

Correct Answers: C

5: If a DHCP server does not exist on a network, the Ethernet port on an autonomous mode MSM Access Point would be assigned a default IP address of 192.168.1.1. Given this information, which statement is correct?

- A.An internal DHCP server in the MSM Access Point can be configured to assign any appropriate IP Address to the port.
- B.An internal dip switch can be configured to change the default IP address of the Ethernet port.
- C.An autonomous mode MSM Access Point can be ordered with the option of a different Default IP Address that could be assigned to its Ethernet port.

D. Without an external DHCP server, the port will always remain at 192.168.1.1.

Correct Answers: D

6: How many Virtual Service Communities (VSCs) does the M110 support?

A.1

B.2

C.3

D.4

Correct Answers: B

7: How does a client associated to an MSM Access Point receive its DHCP IP Address?

A. from either the AP's internal DHCP server or an external DHCP server

B. it cannot receive a DHCP IP Address and a static IP Address is required

C. through an external DHCP server

D. with the AP's internal DHCP server

Correct Answers: C

8: On the MSM710, PoE can power the device from which port?

A. port 1

B. Internet port

C. LAN port

D. only as a backup to the direct DC power adapter

Correct Answers: C

9: Which 802.11n frequency ranges are supported on the MSM422? (Select two.)

A. 2.4 GHz

B. 5 GHz

C. 20 MHz

D. 72 MHz

E. 105.7 MHz

Correct Answers: A B

10: What are the characteristics of the MSM422?

A. a/b/g/n, single radio

B. a/b/g/n, triple radio, integrated AP/Controller

C. a/b/g/n, dual radio, mixed radios

D. a/b/g, dual radio, mixed radios

Correct Answers: C