

Vendor: HP

Exam Code: HP2-Z33

**Exam Name:** HP Unified Wired-Wireless Networks and BYOD

Version: DEMO

## **QUESTION 1**

An administrator changes the setting for VLAN 200 on an HP 830 switch from tagged to untagged. How will this change affect the traffic sent over VLAN 200?

- A. Traffic sent over VLAN 200 will be forwarded to untagged VLAN 1.
- B. Tagged management traffic can no longer be sent on VLAN 200.
- C. Traffic sent over VLAN 200 will have the 802.1Q tag removed.
- D. Tagged traffic sent over VLAN 200 will be forwarded without changing the 802.1Q tag.

#### Answer: D

#### **QUESTION 2**

A branch location is deploying standalone wireless access points (APs). What can be used to configure and manage these APs? (Select two.)

- A. Access Controller
- B. Web interface
- C. IMC/UAM
- D. IMC/EAD
- E. CLI

### Answer: BE

#### **QUESTION 3**

When accessing the wireless network in 802.1X with EAP-TLS, what do the user endpoints require?

- A. username and password of the user's account
- B. client certificate or root certificate
- C. client certificate and root certificate
- D. MS-CHAPV2 to be configured

#### Answer: C

#### **QUESTION 4**

An organization wants to upgrade their wireless network to allow employees to connect using their 802.11ac enabled devices. Which HP access points meet this requirement?

- A. HP 425
- B. HPMSM466
- C. HP MSM430
- D. HP 560

#### Answer: D

#### **QUESTION 5**

An organization implements an N+1 redundancy for its access controllers (ACs). When the primary AC fails, the access points (APs) successfully fail over to the standby AC. However, when the failed AC comes back in to service, the APs do not switch back to the original AC.

What could cause this to happen?

- A. AP Connection priority on the primary AC is not set to 1.
- B. APs determine which AC to connect to based on load.
- C. APs do not fail back to the original AC.
- D. AP Connection priority on the primary AC is not set to 7.

#### Answer: D

## **QUESTION 6**

A customer is planning to deploy HP MSM466-R access points in an extreme cold environment to interconnect to the Unified Wired-WLAN Module in the HP switch. Which requirement is needed to accomplish this?

- A. NEMA 4X enclosures should be used to house the access points.
- B. Switch ports must support PoE.
- C. PoE redundancy must be enabled on the interface.
- D. Access Point must deploy internal antennas.

## Answer: C

#### **Explanation:**

Preventing untagged packets on the physical interface--If you use subinterfaces, you typically do not also want the physical interface to pass traffic, because the physical interface passes untagged packets. This property is also true for the active physical interface in a redundant interface pair. Because the physical or redundant interface must be enabled for the subinterface to pass traffic, ensure that the physical or redundant interface does not pass traffic by leaving out the nameif command. If you want to let the physical or redundant interface pass untagged packets, you can configure the nameif command as usual. See the "Completing Interface Configuration (All Models)" section for more information about completing the interface configuration.

## **QUESTION 7**

What is an advantage of the HP IMC Wireless Service Manager (WSM)?

- A. An organization can centrally configure WLAN deployments of up to 10,000 FIT access points.
- B. An organization can centrally manage WLAN deployments of up to 5,000 FIT access points.
- C. An organization can configure switches, routers, and access controllers from a central location.
- D. An organization can manage guest access through the command line interface.

#### Answer: A

#### **QUESTION 8**

In 802.11n, what does fat channel intolerance indicate?

- A. Clients hearing this information must transmit in the secondary channel only.
- B. Both the clients and access points hearing this information must no longer aggregate MPDU frames.
- C. Access points hearing this information must use the default 40 MHz channel bandwidth.

**★** Instant Download **★** PDF And VCE **★** 100% Passing Guarantee **★** 100% Money Back Guarantee

D. Access points hearing this information must prohibit the use of 40 MHz channels.

Answer: D

**★** Instant Download **★** PDF And VCE **★** 100% Passing Guarantee **★** 100% Money Back Guarantee

# Thank You for Trying Our Product

## Lead2pass Certification Exam Features:

- ★ More than 99,900 Satisfied Customers Worldwide.
- ★ Average 99.9% Success Rate.
- ★ Free Update to match latest and real exam scenarios.
- ★ Instant Download Access! No Setup required.
- ★ Questions & Answers are downloadable in PDF format and VCE test engine format.



- ★ Multi-Platform capabilities Windows, Laptop, Mac, Android, iPhone, iPod, iPad.
- ★ 100% Guaranteed Success or 100% Money Back Guarantee.
- ★ Fast, helpful support 24x7.

View list of all certification exams: <u>http://www.lead2pass.com/all-products.html</u>



10% Discount Coupon Code: ASTR14