



**Vendor:** Cisco

**Exam Code:** 642-973

**Exam Name:** Cisco Data Center Networking Infrastructure  
Support - 1 (DCNIS1)

**Version:** DEMO

### QUESTION 1

Which command is used to enable Cisco NSF for BGP?

- A. 6500(config-router)# bgp graceful-restart
- B. 6500(config-router)# bgp nsf
- C. 6500(config)# bgp enable nsf
- D. 6500(config-router)# enable nsf-capable
- E. 6500(config-router)# nsf

**Answer:** A

### QUESTION 2

You are using RPR. A switchover event will be triggered if either of which two of these fails? (Choose two.)

- A. an administratively monitored line card
- B. a service module
- C. a DFC on a monitored line card
- D. an inter-supervisor clock synchronization
- E. an active supervisor MSFC

**Answer:** DE

### QUESTION 3

Which three of these are examples of FHRPs? (Choose three.)

- A. HSRP
- B. proxy ARP
- C. IRDP
- D. VRRP
- E. GLBP
- F. RIP

**Answer:** ADE

### QUESTION 4

A customer has installed an FWSM in the data center. Which feature must be configured to enable FTP to work?

- A. dynamic NAT
- B. dynamic PAT
- C. access lists
- D. transparent mode
- E. deep packet inspection

**Answer:** E

**QUESTION 5**

Which ingress QoS trust setting sets the CoS or ToS values of any frame entering that port to zero?

- A. trust CoS
- B. trust IP precedence
- C. untrusted
- D. trust DSCP

**Answer: C**

**QUESTION 6**

In a Cisco Catalyst 6500 Series Switch, which engine is required in order to use the distributed Cisco Express Forwarding architecture?

- A. DFC
- B. PFC3A
- C. MSFC3
- D. PFC3B
- E. PFC3BXL

**Answer: A**

**QUESTION 7**

Which two features make up the fault management framework? (Choose two.)

- A. CiscoWorks application
- B. Generic Online Diagnostics
- C. Soft high availability
- D. HP OpenView
- E. CiscoWork Resource Management Essentials

**Answer: BC**

**QUESTION 8**

Which command is used to enable Cisco NSF for EIGRP?

- A. 6500(config-router)# eigrp nsf
- B. 6500(config)# eigrp enable nsf
- C. 6500(config-router)# enable nsf-capable
- D. 6500(config-router)# nsf

**Answer: D**

**QUESTION 9**

Which NAM data-collection method will provide a summary report of utilization and error rates on each switch interface?

- A. SPAN
- B. VACLs
- C. mini-RMON
- D. core monitoring

**Answer: C**

**QUESTION 10**

Which command can be used to regain access to a non-responding Cisco NAM in slot 3?

- A. module slot 3 reset
- B. reload module slot 3
- C. slot 3 reload
- D. hw-module module 3 reset

**Answer: D**

**QUESTION 11**

What must be configured on the FWSM to forward traffic to a filtering server?

- A. the filtering server as an authentication provider (aaa-server)
- B. all web traffic so that it is directed only to the filtering server (access-list)
- C. all HTTP requests so that they are redirected to the filtering server (fixup protocol)
- D. all HTTP requests so that they are sent to the filtering server (url-server)

**Answer: D**

**QUESTION 12**

HSRP active and standby routers send hello messages to which multicast address?

- A. IP address 224.0.0.18, IP protocol number 112
- B. IP address 224.0.0.2, UDP port number 2000
- C. IP address 224.0.0.2, UDP port number 1985
- D. IP address 224.0.0.102, UDP port number 3222

**Answer: C**

**QUESTION 13**

What must be configured on the NAM to allow an NMS to access the NAM?

- A. VACLs
- B. HTTPS service
- C. SNMP community strings
- D. TACACS+ authentication

**Answer: C**

**QUESTION 14**

What must you do to enable HTTPS as the access protocol on the NAM?

- A. Enable the HTTP server, then enable the SSL service.
- B. Install a strong crypto patch on the NAM, then enable the HTTPS server.
- C. Ensure that 128-bit cryptography is enabled, then enable the HTTPS server.
- D. Enable the HTTP server, then issue the http secure server enable command.

**Answer: B**

**QUESTION 15**

Which of these actions must be taken in order to support an EEM script on a system that is enabled for Cisco Catalyst 6500 VSS 1440?

- A. The EEM script must be uploaded via CiscoWorks.
- B. The EEM script must be loaded to both supervisor modules.
- C. The EEM script must be uploaded on the active supervisor module only.
- D. VSS must be disabled, the EEM script uploaded, and VSS re-enabled.

**Answer: B**

## Thank You for Trying Our Product

### Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER  
NETWORKS



EMC<sup>2</sup>  
where information lives<sup>®</sup>

**10% Discount Coupon Code: ASTR14**