



Vendor: Hitachi

Exam Code: HH0-210

Exam Name: HDS Certified Implementer - Enterprise

Version: DEMO

QUESTION 1

A customer is using a Hitachi Enterprise storage system with clustered servers in an active/passive relationship. What must be done in Hitachi Dynamic Link Manager (HDLM) to ensure that the status of inactive paths on both passive and active nodes is monitored regularly?

- A. Switch on Auto Failback.
- B. Switch on Path Health Check.
- C. Set the reservation level to 2.
- D. Set up Intermittent Error Monitoring.

Answer: B

QUESTION 2

What are two prerequisites for virtualizing volumes on a VSP? (Choose two.)

- A. Shared memory must be reserved for external storage operations.
- B. The external storage system must be connected to one or more external ports of the VSP.
- C. A CLPR must be created for the external storage.
- D. The Universal Volume Manager license must be installed in the VSP.

Answer: BD

QUESTION 3

A customer is deploying a new database that will have weekly hot spots requiring higher levels of performance. Which two features of Hitachi Dynamic Tiering would help them? (Choose two.)

- A. thick provisioning
- B. 36 MB pages
- C. wide striping
- D. multi-tier pools

Answer: CD

QUESTION 4

A customer wants to know how to use the audit log for Storage Navigator. Which two statements are true? (Choose two.)

- A. The audit log is stored in the Web Console.
- B. The audit log can be accessed from Storage Navigator.
- C. The audit log is only viewable by the root user.
- D. The audit log can be downloaded for offline viewing.

Answer: BD

QUESTION 5

An application running on a Windows server connected to a Hitachi Enterprise storage system with two paths is generating mostly sequential I/O. Which algorithm should be set in Hitachi Dynamic Link Manager (HDLM) on that server?

- A. Least Blocks
- B. Round Robin
- C. Sequential Blocks
- D. Extended Least I/Os

Answer: D

QUESTION 6

Which three operations are allowed after activating LUN security on a VSP Fibre Channel (FC) port? (Choose three.)

- A. Add multiple WWNs to one Host Group.
- B. Add a LDEV to two different Host Groups on the same FC port.
- C. Create a Host Group with two different Host connection modes.
- D. Add the same WWN to two different Host Groups on the same FC port.
- E. Create host groups with different Host connection modes on the same FC port.

Answer: ABE

QUESTION 7

Your customer wants to connect multiple servers with different operating systems to the same port on a VSP. What is the first step when configuring the port?

- A. Map a LUN.
- B. Register a WWPN.
- C. Enable Port Security.
- D. Create a Host Group.

Answer: C

QUESTION 8

What must be installed on an AIX server prior to a Hitachi Dynamic Link Manager (HDLM) installation?

- A. MPXIO
- B. HACMP
- C. Hitachi ODM
- D. Hitachi Tuning Manager agent

Answer: C

QUESTION 9

A VSP customer is attaching new SUSE Linux servers to their SAN. What are two configuration requirements? (Choose two.)

- A. The queue depth per VSP LUN must not exceed 32.
- B. The queue depth per VSP LUN must be at least 8.
- C. The queue depth per VSP port must not exceed 2048.
- D. The queue depth per VSP port must not exceed 1024.

Answer: AC

QUESTION 10

What are two ways to ensure secure access to storage through a fabric? (Choose two.)

- A. Use SNMP.
- B. Use zoning.
- C. Use Host Group security.
- D. Use port security on the switch(es).

Answer: BC

QUESTION 11

What are two effects of configuring LUN security on a VSP? (Choose two.)

- A. The secured LUNs will be write protected.
- B. Un-registered Open Systems hosts cannot access the data on the secured LUNs.
- C. If LUN security is applied to a particular port, only hosts with the same operating system installed can connect to that port.
- D. If LUN security is applied to a particular port, that port can only be accessed from hosts registered within this port's Host Groups.

Answer: BD

QUESTION 12

A customer wants to add a second DKC to a VSP. Which three hardware features must be installed in the second DKC? (Choose three.)

- A. Hub
- B. VSD
- C. CMA
- D. ESW
- E. DKA

Answer: ABD

QUESTION 13

When is a microcode exchange process complete on a VSP?

- A. After the SVP has rebooted.

- B. When all I/Os resume across all the mapped storage paths.
- C. When the 'Ready' LED turns green.
- D. When the message normal End is displayed. When the message normal End is displayed.

Answer: D

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



Microsoft



ORACLE



CITRIX



JUNIPER
NETWORKS



EMC²
where information lives®

10% Discount Coupon Code: ASTR14