

Vendor: Juniper

Exam Code: JN0-347

**Exam Name:** Enterprise Routing and Switching, Specialist (JNCIS-ENT)

Version: DEMO

#### **QUESTION 1**

Which protocol prevents loops and calculates the best path through a switched network that contains redundant paths?

- A. VRRP
- B. STP
- C. DHCP
- D. IS-IS

# Answer: B

#### **QUESTION 2**

Click the Exhibit button.

user@switch> show spanning-tree bridge	
STP bridge parameters	
Context ID	: 0
Enabled protocol	: RSTP
Root ID	: 4096.00:19:e2:55:36:00
Root cost	: 40000
Root port	: ge-0/0/13.0
Hello time	: 2 seconds
Maximum age	: 20 seconds
Forward delay	: 15 seconds
Message age	: 2
Number of topology changes	: 2
Time since last topology change	: 72 seconds
Local parameters	
Bridge ID	: 32768.00:19:e2:55:1d:40
Extended system ID	: 0
Internal instance ID	: 0

Referring to the outputs shown in the exhibit, which statement is correct?

- A. The switch is the only switch in the RSTP topology.
- B. The switch's bridge priority is 4k.
- C. The switch's bridge priority is 16k.
- D. The switch is not the root bridge.

# Answer: D

#### **QUESTION 3**

A customer discovered that a significant outage was caused by an unauthorized Ethernet switching device attached to the network. In this scenario, which two actions would solve this problem? (Choose two.)

- A. Enable 802.1x.
- B. Enable persistent MAC learning.
- C. Enable dynamic ARP inspection.
- D. Enable storm control.

### Answer: AB

# **QUESTION 4**

Click the Exhibit button.

```
[edit]
user@host# show interfaces
ge-0/0/1 {
     description "Link to R2";
     mtu 1476;
     unit 0 {
          family inet {
               address 192.168.6.1/30;
          family iso;
     }
1
100 {
     unit 0 {
          family inet;
          family iso {
               address 49.0002.0000.0000.0001.00;
          1
     }
}
[edit]
user@host# show protocols isis
interface ge-0/0/1.0;
interface lo0.0;
[edit]
user@host#
```

The IS-IS adjacency between routers R1 and R2 will not establish. Referring to exhibit, what is the problem?

- A. The ISO address is not configured on interface ge-0/0/1.
- B. Thelevel is not configured underprotocols isis.
- C. The IP address is not configured on interface Io0.
- D. The link MTU is too small on interface ge-0/0/1.

# Answer: A

# **QUESTION 5**

Which two statements are true about nonstop bridging (NSB)? (Choose two.)

- A. NSB does not require all participating Routing Engines to run the same version of the Junos OS.
- B. NSB can be enabled under theprotocols layer2-controlhierarchy.
- C. NSB requires you to configure gracefulRouting Engine switchover (GRES).
- D. NSB does not require you to configure graceful Routing Engine switchover (GRES).

# Answer: BC

# **QUESTION 6**

Which Junos feature allows you to combine multiple interfaces into a single bundle?

- A. VRRP
- B. Virtual Chassis
- C. LAG
- D. NSB

#### Answer: C

#### **QUESTION 7**

What is the default BGP group type on a Junos device?

- A. internal
- B. external
- C. multihop
- D. null

#### Answer: B

#### **QUESTION 8**

You received an alert from your monitoring system that the master Routing Engine (RE) on an EX4300 switch in a virtual chassis has hardware issues and might need to be replaced. Because the switch already had graceful Routing Engine switchover (GRES) enabled and configured, you must perform a manual switchover to the backup RE to avoid disruption. Which command would be used to perform the manual RE switchover?

- A. Log in to the backup RE and issue therequest chassis-control operation command.
- B. Log in to the backup RE and issue therequest chassis routing-engine master switchoperation command.
- C. Log in to the backup RE and issue therequest chassis routing-engine master acquireoperation command.
- D. Log in to the backup RE and issue therequest iccp-service operation command.

# Answer: B

#### **QUESTION 9**

Which two statements are true about Virtual Chassis? (Choose two.)

- A. It is possible to automatically update the Junos OS on newly added members to participate in the Virtual Chassis
- B. A software version mismatch on a newlyadded member must be placed in linecard mode.
- C. Virtual Chassis members use VCCP to create a loop-free topology.
- D. The member ID is not preserved through reboots.

# Answer: AC

**★** Instant Download **★** PDF And VCE **★** 100% Passing Guarantee **★** 100% Money Back Guarantee

# Thank You for Trying Our Product

# Lead2pass Certification Exam Features:

- ★ More than 99,900 Satisfied Customers Worldwide.
- ★ Average 99.9% Success Rate.
- ★ Free Update to match latest and real exam scenarios.
- ★ Instant Download Access! No Setup required.
- ★ Questions & Answers are downloadable in PDF format and
   VCE test engine format.



- ★ Multi-Platform capabilities Windows, Laptop, Mac, Android, iPhone, iPod, iPad.
- ★ 100% Guaranteed Success or 100% Money Back Guarantee.
- ★ Fast, helpful support 24x7.

View list of all certification exams: <u>http://www.lead2pass.com/all-products.html</u>



10% Discount Coupon Code: ASTR14