



Vendor: Citrix

Exam Code: 1Y0-230

Exam Name: Citrix NetScaler 12 Essentials and Unified Gateway

Version: DEMO

QUESTION 1

Scenario: A Citrix Administrator entered the command-line interface commands below to prevent IP address 10.10.10.100 from accessing the NetScaler on port 80.

```
add simpleacl rule1 DENY -srcIP 10.10.10.100 -TTL 600
add simpleacl rule2 DENY -srcIP 10.10.10.100 -destPort 80
add ns acl rule1 DENY -srcIP 10.10.10.100 -priority 10
add ns acl rule2 DENY -srcIP 10.10.10.100 -priority 100
apply ns acls
```

Which Access Control List (ACL) will the NetScaler use to deny the IP address?

- A. add ns acl rule1 DENY -srcIP 10.10.10.100 -priority 10
- B. add simpleacl rule1 DENY -srcIP 10.10.10.100 -TTL 600
- C. add simpleacl rule2 DENY -srcIP 10.10.10.100 -destPort 80
- D. add ns acl rule2 DENY -srcIP 10.10.10.100 -priority 100

Answer: C

Explanation:

<https://docs.citrix.com/ko-kr/netscaler/11/reference/netscaler-command-reference/ns-simpleacl.html>

QUESTION 2

A Citrix Administrator needs to create a customized blacklist of IP addresses to supplement the Webroot reputation check, and in order to have stricter access through NetScaler. How can the administrator create this blacklist?

- A. Create several extended Access Control List policies
- B. Create a data set for IPv4 address matching.
- C. C. Enable MAC-based Forwarding
- D. Create several simple Access Control List policies.

Answer: A

QUESTION 3

Scenario: A NetScaler has two interlaces as 1/1 and 1/2 with MAC-based Forwarding enabled below are the specifications

```
- Interlace 1/1 and IP 192 168 10.10 is bound to VLAN 10
- On Interlace 1/2 VLAN 20 and VLAN 30 are tagged
- VLAN 20 is bound to IP 192.168 20 10 and VLAN 30 is bound to
192.168.30 10
```

The NetScaler receives a packet for VIP 192 168.30.30 on interface 1/1. Which interlace of NetScaler will send a reply back in this environment?

- A. Interface 1/1
- B. NetScaler will drop the packet received on interface 1/1
- C. Interface 1/2
- D. NetScaler will reply on interfaces 1/1 and 1/2

Answer: A

Explanation:

<https://docs.citrix.com/en-us/netScaler/12/networking/interfaces/configuring-mac-based-forwarding.html>

QUESTION 4

Scenario: A Citrix administrator configured a new NetScaler Unified Gateway. The administrator would like to see what Endpoint Analysis and Single Sign-on failures have occurred since implementing the new Gateway.

Which tool can the administrator use to see this data?

- A. NetScaler Dashboard
- B. MAS Gateway Insight
- C. aaad.debug
- D. MAS Security Insight

Answer: B

QUESTION 5

Which two options should a Citrix Administrator consider when adding a secondary device in a high availability (HA) pair? (Choose two.)

- A. The Independent Network Configuration (INC) mode should be enabled.
- B. Both the devices should have different SNIP addresses.
- C. The nsroot password should be same on both nodes.
- D. HA Monitoring should be disabled on all the unused interfaces.
- E. Configure the HA status of the Primary Node as STAYPRIMARY.

Answer: CD

Explanation:

<https://support.citrix.com/article/CTX116748>

QUESTION 6

Scenario: A Citrix Administrator suspects an attack on a load-balancing virtual server. The administrator needs to restrict access to the load-balancing virtual server (192.168.100.25) for 10 minutes.

Which Access Control List (ACL) will help to accomplish this requirement?

- A. add ns acl rule1 DENY -destIP 192.168.100.25 -TTL 600000
- B. add simpleacl rule1 DENY -srcIP 192.168.100.25 -TTL 600
- C. add ns acl rule1 DENY -destIP 192.168.100.25 -TTL 600
- D. add simpleacl rule1 DENY -srcIP 192.168.100.25 -TTL 600000

Answer: C

QUESTION 7

Scenario: A Citrix Administrator has a NetScaler SDX appliance with several instances configured. The administrator needs one instance with two interfaces connected to forward packets that are NOT destined for its MAC address. Hence, the administrator has enabled Layer

2 mode. After enabling Layer 2 mode, the administrator found the interface status going up and down.

What can the administrator perform to resolve this issue?

- A. Disable Layer 2 mode on a NetScaler instance.
- B. Enable MAC-based Forwarding mode.
- C. Enable tagging on all interfaces.
- D. Enable Layer 3 mode along with Layer 2 mode.

Answer: C

Explanation:

<https://docs.citrix.com/en-us/sdx/10-1/sdx-ag-config-manage-ns-instance-wrapper-tsk/sdx-ag-config-l2-mode-on-ns-instance-tsk.html>

QUESTION 8

Which two features can a Citrix Administrator use to allow secure external access to a sensitive company web server that is load-balanced by the NetScaler? (Choose two.)

- A. ICA proxy
- B. Integrated caching
- C. Application Firewall
- D. AppFlow
- E. AAA

Answer: CE

Explanation:

<https://www.google.com.br/amp/s/blogs.serioustek.net/post/2017/11/15/netcaler-nfactor-authentication/amp>

QUESTION 9

Which two components need to be configured for SmartAccess? (Choose two.)

- A. Configuration logging
- B. XenDesktop policies
- C. XML Trust
- D. StoreFront server groups

Answer: BC

Explanation:

<http://www.carlstalhood.com/smartaccess-smartcontrol-netscaler-11/#smartaccess>

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



10% Discount Coupon Code: ASTR14