



**Vendor:** Juniper

**Exam Code:** JN0-635

**Exam Name:** Security, Professional (JNCIP-SEC)

**Version:** 20.111

### QUESTION 1

Which interface family is required for Layer 2 transparent mode on SRX Series devices?

- A. LLDP
- B. Ethernet switching
- C. inet
- D. VPLS

**Answer: B**

### QUESTION 2

Click the Exhibit button.

```
user@srx> show chassis cluster interfaces
Control link status: Up

Control interfaces:
      Index      Interface      Monitored-Status      Internal-SA      Security
      0          em0          Up                    Disabled        Enabled

Fabric link status: Up

...
```

Referring to the exhibit, which statement is true?

- A. ARP security is securing data across the control interface
- B. IPsec is securing data across the control interface
- C. SSH is securing data across the control interface
- D. MACsec is securing data across the control interface

**Answer: D**

**Explanation:**

[https://www.juniper.net/documentation/en\\_US/junos/topics/reference/command-summary/show-chassis-cluster-interfaces.html](https://www.juniper.net/documentation/en_US/junos/topics/reference/command-summary/show-chassis-cluster-interfaces.html)

### QUESTION 3

You have configured three logical tunnel interfaces in a tenant system on an SRX1500 device. When committing the configuration, the commit fails.

In this scenario, what would cause this problem?

- A. There is no GRE tunnel between the tenant system and master system allowing SSH traffic
- B. There is no VPLS switch on the tenant system containing a peer lt-0/0/0 interface
- C. The SRX1500 device does not support more than two logical interfaces per tenant system
- D. The SRX1500 device requires a tunnel PIC to allow for logical tunnel interfaces

**Answer: B**

**Explanation:**

[https://www.juniper.net/documentation/en\\_US/junos/topics/topic-map/logical-systems-overview.html](https://www.juniper.net/documentation/en_US/junos/topics/topic-map/logical-systems-overview.html)

#### QUESTION 4

You are asked to merge to corporate network with the network from a recently acquired company. Both networks use the same private IPv4 address space (172.25.126.0/24). An SRX Series device servers as the gateway for each network.

Which solution allows you to merge the two networks without modifying the current address assignments?

- A. persistent NAT
- B. NAT46
- C. source NAT
- D. double NAT

**Answer:** D

**Explanation:**

<https://kb.juniper.net/InfoCenter/index?page=content&id=KB21286>

#### QUESTION 5

You have set up Security Director with Policy Enforcer and have configured 12 third-party feeds and a Sky ATP feed. You are also injecting 16 feeds using the available open API. You want to add another compatible feed using the available open API, but Policy Enforcer is not receiving the new feed.

What is the problem in this scenario?

- A. You must wait 48 hours for the feed to update
- B. You cannot add more than 16 feeds through the available open API
- C. You have reached the maximum limit of 29 total feeds
- D. You cannot add more than 16 feeds with the available open API

**Answer:** C

**Explanation:**

[https://www.juniper.net/documentation/en\\_US/release-independent/sky-atp/information-products/pathway-pages/sky-atp-admin-guide.pdf](https://www.juniper.net/documentation/en_US/release-independent/sky-atp/information-products/pathway-pages/sky-atp-admin-guide.pdf) page 110

#### QUESTION 6

Which three types of peer devices are supported for CoS-based IPsec VPNs? (Choose three.)

- A. branch SRX Series device
- B. third-party device
- C. cSRX
- D. high-end SRX Series device
- E. vSRX

**Answer:** ADE

**Explanation:**

[https://www.juniper.net/documentation/en\\_US/junos/topics/topic-map/secuirty-cos-based-ipsec-vpns.html](https://www.juniper.net/documentation/en_US/junos/topics/topic-map/secuirty-cos-based-ipsec-vpns.html)

#### QUESTION 7

You are asked to configure a new SRX Series CPE device at a remote office. The device must participate in forwarding MPLS and IPsec traffic.

Which two statements are true regarding this implementation? (Choose two.)

- A. Host inbound traffic must not be processed by the flow module
- B. Host inbound traffic must be processed by the flow module
- C. The SRX Series device can process both MPLS and IPsec with default traffic handling
- D. A firewall filter must be configured to enable packet mode forwarding

**Answer:** AD

**Explanation:**

[https://www.juniper.net/documentation/en\\_US/junos/topics/topic-map/security-packet-based-forwarding.html](https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-packet-based-forwarding.html)

#### QUESTION 8

Which three roles or protocols are required when configuring an ADVPN? (Choose three.)

- A. OSPF
- B. shortcut partner
- C. shortcut suggester
- D. IKEv1
- E. BGP

**Answer:** ABC

**Explanation:**

[https://www.juniper.net/documentation/en\\_US/junos/topics/topic-map/security-auto-discovery-vpns.html](https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-auto-discovery-vpns.html)

#### QUESTION 9

You must troubleshoot ongoing problems with IPsec tunnels and security policy processing. Your network consists of SRX340s and SRX5600s.

In this scenario, which two statements are true? (Choose two.)

- A. IPsec logs are written to the kmd log file by default
- B. IKE logs are written to the messages log file by default
- C. You must enable data plane logging on the SRX340 devices to generate security policy logs
- D. You must enable data plane logging on the SRX5600 devices to generate security policy logs

**Answer:** AD

#### QUESTION 10

Click the Exhibit button.

```
user@host> telnet 172.20.202.10
Connected to 172.20.202.10.
Escape character is '^]'.
remote-device (ttyp1)
login:

user@srx> show security flow session application telnet
Session ID: 68748, Policy name: FBF-Internet/11, Timeout: 1722, Valid
  In: 172.20.201.10/55530 --> 172.20.202.10/23;tcp, Conn Tag: 0x0, If: ge-
0/0/5.0,
  Pkts: 28, Bytes: 1624,
  Out: 172.20.202.10/23 --> 172.20.201.10/55530;tcp, Conn Tag: 0x0, If:
ge-0/0/1.0, Pkts: 22, Bytes: 1418,
Total sessions: 1
```

You are implementing a new branch site and want to ensure Internet traffic is sent directly to your ISP and other traffic is sent to your company headquarters. You have configured filter-based forwarding to accomplish this objective. You verify proper functionality using the outputs shown in the exhibit.

Which two statements are true in this scenario? (Choose two.)

- A. The session utilizes one routing instance
- B. The ge-0/0/5 and ge-0/0/1 interfaces must reside in a single security zone
- C. The ge-0/0/5 and ge-0/0/1 interfaces can reside in different security zones
- D. The session utilizes two routing instances

**Answer:** AC

## Thank You for Trying Our Product

### Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



**10% Discount Coupon Code: ASTR14**