

Arista

ACE-A1.2 Exam

Arista Certified Engineering Associate Exam

Question: 1

On EOS 4.13.1F, which of the following statements are true in regards to Arista's Tap Aggregation feature? (Select two)

- A. Tap ports are send only.
- B. Tap ports are receive only.
- C. Tool ports are send only.
- D. Tool ports are receive only.

Answer: A,D

Question: 2

Where does About look for the boot system image at boot time?

- A. At the location specified in the running-config
- B. At the location specified in the startup-config
- C. At the location specified in a file named boot-config on flash:
- D. At the location specified in a file named boot_config on flash:

Answer: C

Question: 3

When ZTP is in enable mode, what triggers ZTP when the switch boots?

- A. A missing or zero-byte SWI image.
- B. A missing or zero-clue administrator.
- C. A missing or zero-byte startup-config file
- D. A missing or zero-byte running-config file

Answer: C

Question: 4

Which of the following are valid Event Manager triggers?

- A. on-boot
- B. on-schedule
- C. on-startup-config
- D. on-reload

Answer: A,C

Question: 5

Which of the following Arista switch series' supports Zero Touch Provisioning (ZTP)?

- A. 7050
- B. 7280E
- C. 7300
- D. 7500E

Answer: D

Question: 6

Which command would you use to change the SSH Idle timeout after entering the 'management ssh' command?

- A. idle-timeout <minutes>
- B. timed <minutes>
- C. timeout <minutes>
- D. ssh-idle <minutes>

Answer: A

Question: 7

What would be the result of issuing a reload command on one of the two switches peered together in an MLAG domain where both switches are running EOS version 4.14.1F?

- A. Dual-homed hosts lose 50% of network capacity through the MLAG domain while the switch reboots
- B. The peer switch also reboots to ensure network stability.
- C. The peer switch sends out gratuitous BPDUs to let the network know that it has assumed the root-bridge role.
- D. Nothing bad ever happens when MLAG is enabled!

Answer: A

Question: 8

On an Arista switch, which port is used to connect a laptop to the switch for initial configuration or password recovery?

- A. Ethernet 1
- B. Console

- C. Management 1
- D. Ethernet 1/1

Answer: A

Question: 9

How many Arista switches may be a part of a single MLAG domain?

- A. 2
- B. 4
- C. 8
- D. 16

Answer: A

Question: 10

Which of the following are not valid boot-config file entries?

- A. NETGW=192.168.1.1
- B. IMAGE-flash:EOS-4.12.1.swi
- C. SWI=flash:EOS-4.12.1.swi
- D. SWIX=flash:EOS-4.12.1.swi

Answer: B
