



Vendor: Splunk

Exam Code: SPLK-4001

Exam Name: Splunk O11y Cloud Certified Metrics User

Version: DEMO

QUESTION 1

Which of the following are true about organization metrics? (select all that apply)

- A. Organization metrics give insights into system usage, system limits, data ingested and token quotas.
- B. Organization metrics count towards custom MTS limits.
- C. Organization metrics are included for free.
- D. A user can plot and alert on them like metrics they send to Splunk Observability Cloud.

Answer: ACD

Explanation:

Organization metrics give insights into system usage, system limits, data ingested and token quotas. Organization metrics are included for free. A user can plot and alert on them like metrics they send to Splunk Observability Cloud. Organization metrics are a set of metrics that Splunk Observability Cloud provides to help you measure your organization's usage of the platform. They include metrics such as:

Ingest metrics: Measure the data you're sending to Infrastructure Monitoring, such as the number of data points you've sent.

App usage metrics: Measure your use of application features, such as the number of dashboards in your organization.

Integration metrics: Measure your use of cloud services integrated with your organization, such as the number of calls to the AWS CloudWatch API.

Resource metrics: Measure your use of resources that you can specify limits for, such as the number of custom metric time series (MTS) you've created.

Organization metrics are not charged and do not count against any system limits. You can view them in built-in charts on the Organization Overview page or in custom charts using the Metric Finder. You can also create alerts based on organization metrics to monitor your usage and performance.

QUESTION 2

Which of the following aggregate analytic functions will allow a user to see the highest or lowest n values of a metric?

- A. Maximum / Minimum
- B. Best/Worst
- C. Exclude / Include
- D. Top / Bottom

Answer: D

Explanation:

Top and bottom are aggregate analytic functions that allow a user to see the highest or lowest n values of a metric. They can be used to select a subset of the time series in the plot by count or by percent. For example, top (5) will show the five time series with the highest values in each time period, while bottom (10%) will show the 10% of time series with the lowest values in each time period.

QUESTION 3

Which of the following are ways to reduce flapping of a detector? (select all that apply)

- A. Configure a duration or percent of duration for the alert.
- B. Establish a reset threshold for the detector.
- C. Enable the anti-flap setting in the detector options menu.

D. Apply a smoothing transformation (like a rolling mean) to the input data for the detector.

Answer: AD

Explanation:

According to the Splunk Lantern article Resolving flapping detectors in Splunk Infrastructure Monitoring, flapping is a phenomenon where alerts fire and clear repeatedly in a short period of time, due to the signal fluctuating around the threshold value. To reduce flapping, the article suggests the following ways:

Configure a duration or percent of duration for the alert: This means that you require the signal to stay above or below the threshold for a certain amount of time or percentage of time before triggering an alert. This can help filter out noise and focus on more persistent issues. Apply a smoothing transformation (like a rolling mean) to the input data for the detector: This means that you replace the original signal with the average of its last several values, where you can specify the window length. This can reduce the impact of a single extreme observation and make the signal less fluctuating.

QUESTION 4

A customer is experiencing an issue where their detector is not sending email notifications but is generating alerts within the Splunk Observability UI. Which of the below is the root cause?

- A. The detector has an incorrect alert rule.
- B. The detector has an incorrect signal,
- C. The detector is disabled.
- D. The detector has a muting rule.

Answer: D

Explanation:

The detector has a muting rule. A muting rule is a way to temporarily stop a detector from sending notifications for certain alerts, without disabling the detector or changing its alert conditions. A muting rule can be useful when you want to avoid alert noise during planned maintenance, testing, or other situations where you expect the metrics to deviate from normal.

When a detector has a muting rule, it will still generate alerts within the Splunk Observability UI, but it will not send email notifications or any other types of notifications that you have configured for the detector. You can see if a detector has a muting rule by looking at the Muting Rules tab on the detector page. You can also create, edit, or delete muting rules from there.

QUESTION 5

To smooth a very spiky `cpu.utilization` metric, what is the correct analytic function to better see if the `cpu.utilization` for servers is trending up over time?

- A. Rate/Sec
- B. Median
- C. Mean (by host)
- D. Mean (Transformation)

Answer: D

Explanation:

According to the web search results, a mean transformation is an analytic function that returns the average value of a metric or a dimension over a specified time interval. A mean transformation can be used to smooth a very spiky metric, such as `cpu.utilization`, by reducing the impact of outliers and noise. A mean transformation can also help to see if the metric is trending up or down over time, by showing the general direction of the average value. For example, to

smooth the cpu.utilization metric and see if it is trending up over time, you can use the following SignalFlow code:

```
mean(1h, counters("cpu.utilization"))
```

This will return the average value of the cpu.utilization counter metric for each metric time series (MTS) over the last hour. You can then use a chart to visualize the results and compare the mean values across different MTS.

QUESTION 6

What happens when the limit of allowed dimensions is exceeded for an MTS?

- A. The additional dimensions are dropped.
- B. The datapoint is averaged.
- C. The datapoint is updated.
- D. The datapoint is dropped.

Answer: A

Explanation:

According to the web search results, dimensions are metadata in the form of key-value pairs that monitoring software sends in along with the metrics. The set of metric time series (MTS) dimensions sent during ingest is used, along with the metric name, to uniquely identify an MTS. Splunk Observability Cloud has a limit of 36 unique dimensions per MTS. If the limit of allowed dimensions is exceeded for an MTS, the additional dimensions are dropped and not stored or indexed by Observability Cloud. This means that the data point is still ingested, but without the extra dimensions. Therefore, option A is correct.

QUESTION 7

Changes to which type of metadata result in a new metric time series?

- A. Dimensions
- B. Properties
- C. Sources
- D. Tags

Answer: A

Explanation:

Dimensions are metadata in the form of key-value pairs that are sent along with the metrics at the time of ingest. They provide additional information about the metric, such as the name of the host that sent the metric, or the location of the server. Along with the metric name, they uniquely identify a metric time series (MTS).

Changes to dimensions result in a new MTS, because they create a different combination of metric name and dimensions. For example, if you change the hostname dimension from host1 to host, you will create a new MTS for the same metric name.

Properties, sources, and tags are other types of metadata that can be applied to existing MTSES after ingest. They do not contribute to uniquely identify an MTS, and they do not create a new MTS when changed.

QUESTION 8

The built-in Kubernetes Navigator includes which of the following?

- A. Map, Nodes, Workloads, Node Detail, Workload Detail, Group Detail, Container Detail
- B. Map, Nodes, Processors, Node Detail, Workload Detail, Pod Detail, Container Detail
- C. Map, Clusters, Workloads, Node Detail, Workload Detail, Pod Detail, Container Detail
- D. Map, Nodes, Workloads, Node Detail, Workload Detail, Pod Detail, Container Detail

Answer: D

Explanation:

The built-in Kubernetes Navigator is a feature of Splunk Observability Cloud that provides a comprehensive and intuitive way to monitor the performance and health of Kubernetes environments. It includes the following views:

Map: A graphical representation of the Kubernetes cluster topology, showing the relationships and dependencies among nodes, pods, containers, and services. You can use the map to quickly identify and troubleshoot issues in your cluster.

Nodes: A tabular view of all the nodes in your cluster, showing key metrics such as CPU utilization, memory usage, disk usage, and network traffic. You can use the nodes view to compare and analyze the performance of different nodes.

Workloads: A tabular view of all the workloads in your cluster, showing key metrics such as CPU utilization, memory usage, network traffic, and error rate. You can use the workloads view to compare and analyze the performance of different workloads, such as deployments, stateful sets, daemon sets, or jobs.

Node Detail: A detailed view of a specific node in your cluster, showing key metrics and charts for CPU utilization, memory usage, disk usage, network traffic, and pod count. You can also see the list of pods running on the node and their status. You can use the node detail view to drill down into the performance of a single node.

Workload Detail: A detailed view of a specific workload in your cluster, showing key metrics and charts for CPU utilization, memory usage, network traffic, error rate, and pod count. You can also see the list of pods belonging to the workload and their status. You can use the workload detail view to drill down into the performance of a single workload.

Pod Detail: A detailed view of a specific pod in your cluster, showing key metrics and charts for CPU utilization, memory usage, network traffic, error rate, and container count. You can also see the list of containers within the pod and their status. You can use the pod detail view to drill down into the performance of a single pod.

Container Detail: A detailed view of a specific container in your cluster, showing key metrics and charts for CPU utilization, memory usage, network traffic, error rate, and log events. You can use the container detail view to drill down into the performance of a single container.

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



10% Discount Coupon Code: ASTR14