



Vendor: Dell-EMC

Exam Code: D-PEMX-DY-23

Exam Name: Dell PowerEdge MX Modular Deploy 2023

Version: DEMO

QUESTION 1

What are two considerations when adding an MX760c in a chassis running OME-M firmware earlier than v2.0?

(Select 2)

- A. If the MX760c is a thermally challenged system, the maximum supported ambient temperature cannot be reduced.
- B. If the MX760c is not a thermally challenged system, the sled is going to run as designed.
- C. All the fans on the PowerEdge MX7000 must be Silver Grade.
- D. If the iDRAC of the existing sleds is not at a supported level, ATMOS cannot calculate the maximum cooling.

Answer: AD

QUESTION 2

Which is a logical resource in SmartFabric?

- A. storage
- B. servers
- C. uplinks
- D. switches

Answer: C

QUESTION 3

What type of video connector is available for KVM connectivity on the PowerEdge MX7000 chassis?

- A. Mini-DVI
- B. DisplayPort
- C. VGA
- D. Mini DisplayPort

Answer: D

QUESTION 4

What is the maximum number of mezzanine cards that can be installed in an MX840c?

- A. 6
- B. 5
- C. 3
- D. 8

Answer: A

QUESTION 5

A PowerEdge MX7000 administrator is tasked to perform a chassis update using a catalog. Which source options are used to create the catalog?

- A. Newest validated stacks of chassis firmware on dell.com Latest component firmware versions on dell.com
Network path
- B. Latest component firmware versions on dell.com
Dell Update Package
Network path
- C. Newest validated stacks of chassis firmware on dell.com Dell Update Package
Local Directory path
- D. Newest validated stacks of chassis firmware on dell.com Latest component firmware versions on dell.com
Local Directory path

Answer: A

QUESTION 6

What is a function of the Fabric Resources Director (FReD)?

- A. SAS Expander routing for Fabric C
- B. Hosting OME-M interface
- C. Critical temperature monitoring
- D. Providing QuickSync 2 feature

Answer: C

QUESTION 7

An administrator is sending servers to other individuals but wants to reset the server to the factory default first.

What LifeCycle Controller feature is used to complete this action?

- A. Repurpose or Retire
- B. Set BIOS to defaults
- C. Delete RAID array
- D. RACADM RACRESETCFG

Answer: A

QUESTION 8

What is the connection protocol between FReD and MM?

- A. HDMI
- B. Ethernet
- C. I2C
- D. FC

Answer: C

QUESTION 9

Which two actions are possible using the Chassis Deployment Wizard? (Select 2)

- A. The LCD pin can be configured.
- B. The administrator can use an existing chassis profile to configure the chassis.
- C. The firmware catalog can be configured using the FTP protocol.
- D. The network I/O Module password can be configured.

Answer: BC

QUESTION 10

A customer wants to change the switch operating mode from SmartFabric mode to Full Switch mode. After deleting the fabric in OME-M, what configuration is retained on the switch?

- A. admin password, hostname, management IP Address, and the VLT domain configuration
- B. admin password, hostname, and management IP Address
- C. admin password, hostname, management IP Address, and all port breakout configuration
- D. admin password, hostname, management IP Address, and the VLAN database

Answer: B

QUESTION 11

What is the minimum OME-M version required to use ATMOS?

- A. 1.40.00
- B. 2.00.00
- C. 2.10.00
- D. 1.60.50

Answer: B

QUESTION 12

Which command(s) is supported in the current PowerEdge MX Redfish implementation?

- A. PUT and DELETE
- B. PUT only
- C. HEAD and PUT
- D. GET and DELETE

Answer: D

QUESTION 13

After a main board replacement, the easy restore process was not successful. A system administrator is not able to launch the Virtual Console. What is the cause of this issue?

- A. ActiveX is not installed.
- B. Java is not installed.
- C. Enterprise license is not installed.
- D. KVM is not present.

Answer: C

QUESTION 14

A customer would like to periodically change the iDRAC root password on all the servers in their MCM Group.

What feature in OME-M should they use?

- A. SupportAssist
- B. Resource Pools
- C. Quick Deploy
- D. Chassis Deployment Wizard

Answer: C

QUESTION 15

What is the port configuration of an MX5108n switch?

- A. 16 x internal 25GbE ports
4 x 40GbE QSFP+ ports
2 x 100GbE QSFP28 ports
1 x 10GbE RJ45 Base-T port
- B. 8 x internal 25GbE ports
1 x 40GbE QSFP+ port
2 x 100GbE QSFP28 ports
4 x 10GbE RJ45 Base-T ports
- C. 8 x internal 25GbE ports
2 x 40GbE QSFP+ ports
1 x 100GbE QSFP28 port
4 x 10GbE RJ45 Base-T ports
- D. 16 x internal 25GbE ports
1 x 40GbE QSFP+ port
2 x 100GbE QSFP28 ports
4 x 10GbE RJ45 Base-T ports

Answer: B

QUESTION 16

What item is used to refer to a daisy-chained configuration of a multiple MX7000 chassis environment?

- A. Wired group
- B. Identity group
- C. Chassis group
- D. Physical group

Answer: A

Thank You for Trying Our Product

Lead2pass Certification Exam Features:

- ★ More than **99,900** Satisfied Customers Worldwide.
- ★ Average **99.9%** Success Rate.
- ★ **Free Update** to match latest and real exam scenarios.
- ★ **Instant Download** Access! No Setup required.
- ★ Questions & Answers are downloadable in **PDF** format and **VCE** test engine format.
- ★ Multi-Platform capabilities - **Windows, Laptop, Mac, Android, iPhone, iPod, iPad**.
- ★ **100%** Guaranteed Success or **100%** Money Back Guarantee.
- ★ **Fast**, helpful support **24x7**.



View list of all certification exams: <http://www.lead2pass.com/all-products.html>



10% Discount Coupon Code: ASTR14